

GROWER

IMPLEMENTOS



REMOLQUES



MODELO	G7C5.0	G7C6.0	G7C7.0	G7C9.0	G7C15.0
Carga Fija kg (lb)	5.000 (11.023)	6.000 (13.227)	7.000 (15.432)	9.000 (19.841)	15.000 (33.069)
Potencia CV (Hp)	70(69)	80 (78,9)	80 (78,9)	90 (88,7)	120 (118,3)
Longitud mm (ft)	560 (1,8)	580 (1,9)	600 (2,0)	650 (2,1)	800 (2,6)
Ancho mm (ft)	210 (0,7)	210 (0,7)	210 (0,7)	220 (0,7)	230 (0,8)
Alto mm (ft)	228 (0,7)	228 (0,7)	228 (0,7)	238 (0,8)	252 (0,8)
Peso Operativo kg (lb)	1.700 (3.747)	1.950 (4.299)	2.150 (4.739)	2.300 (5.070)	3.500 (7.716)
Volumen L (gal)	4.000 (1.056)	4.500 (1.188)	5.300 (1.400)	6.800 (1.796)	10.500 (2.773)
Neumáticos	8.25-16-14	9.00-16-14	9.00-20-16	9.00-20-16	9.00-20-16

PLANTADORAS DE MAÍZ



MODELO	G2BCYF-3	G2BCYF-4	G2BCYF-5	G2BCYF-6
Profundidad de siembra mm (in)	30-50 (1,2 - 2,0)	30-50 (1,2 - 2,0)	30-50 (1,2 - 2,0)	30-50 (1,2 - 2,0)
Productividad ha (acre)	0.2-0.3 (0,4 - 0,6)	0.4-0.5 (0,8-1,0)	0.65-0.85 (1,3-1,7)	0.80-1 (1,6-2,0)
Peso operativo kg (lb)	180 (396,8)	230 (507,1)	320 (705)	420 (925,9)
Fallas	3	4	5	6
Capacidad del tanque de fertilizante L (gal)	48 (12,7)	64 (16,9)	80 (21,1)	96 (25,4)
Capacidad del depósito de semillas L (gal)	27 (7,1)	36 (9,5)	64 (16,9)	64 (16,9)
Potencia kw (hp)	8,9-22,4 (11,9-30)	14,9-37,3 (20,0-50,0)	37,3 59,7 (50-80)	37,3-59,7 (50-80)

GRADAS DE DISCOS



MODELO	G1BJX-1.7	G1BJX-2.0	G1BJX-2.2	G1BJX-2.4
Anchura de trabajo m (ft)	1,7 (5,6)	2,0 (6,6)	2,2 (7,2)	2,4 (7,9)
Profundidad de trabajo cm (in)	14-18 (5,5-7,1)	14-18 (5,5-7,1)	14-18 (5,5-7,1)	14-18 (5,5-7,1)
Diámetro de discos mm (in)	560 (22,0)	560 (22,0)	560 (22,0)	560 (22,0)
Cantidad de discos	16	16	20	20
Productividad ha/h (ac/h)	1,3 (2,6)	1,3 (2,6)	1,6 (3,2)	1,6 (3,2)
Longitud mm (ft)	1.960 (6,4)	1.960 (6,4)	1.980 (6,5)	1.980 (6,5)
Ancho mm (ft)	1.880 (6,2)	1.880 (6,2)	2.470 (8,1)	2.470 (8,1)
Alto mm (ft)	1.317 (4,3)	1.317 (4,3)	1.317 (4,3)	1.317 (4,3)
Peso operativo kg (lb)	400 (881,8)	400 (881,8)	463 (1.020)	463 (1.020)
Potencia kw (hp)	33,5-41 (44,9-55)	33,5-41 (44,9-55)	41 (55)	41 (55)

GRADAS DE DISCOS DE TRABAJO PESADO



MODELO	G1BZ-1.8	G1BZ-2.2	G1BZ-2.5	G1BZ-3.0	G1BZ-3.4
Longitud mm (ft)	4.800 (15,7)	4.820 (15,8)	5.320 (17,5)	5.320 (17,5)	5.820 (19,1)
Ancho mm (ft)	2.000 (6,6)	2.440 (8,0)	2.880 (9,4)	3.320 (10,9)	3.760 (12,3)
Alto mm (ft)	1.340 (4,4)	1.340 (4,4)	1.340 (4,4)	1.340 (4,4)	1.340 (4,4)
Peso operativo kg (lb)	1.100 (2.425)	1.300 (2.866)	1.430 (3.152)	1.550 (3.417)	1.700 (3.747)
Anchura de trabajo m (ft)	1,8(5,9)	2,0(6,6)	2,5(8,2)	3,0(9,8)	3,4(11,2)
Profundidad de trabajo cm (in)	20 (7,9)	20 (7,9)	20 (7,9)	20 (7,9)	20 (7,9)
Cantidad de discos	16	20	24	28	32
Diámetro de disco mm (in)	660 (26)	660 (26)	660 (26)	660 (26)	660 (26)
Productividad ha/h (ac/h)	1,1 (2,2)	1,3 (2,6)	1,4 (2,8)	1,7 (3,4)	1,9 (3,8)
Potencia cv (hp)	65-80 (64,1-78,9)	75-90 (73,9-88,7)	80-100 (78,9-98,6)	90-100 (88,7-98,6)	100-120 (98,6-118,3)

PALAS CARGADORAS



MODELO	G554TK-QS	G754TK-QS	G1004TK-QS
Longitud mm (ft)	2.630 (8,6)	2.890 (9,5)	3.000 (9,8)
Ancho mm (ft)	1.670 (5,5)	1.830 (6,0)	2.100 (6,9)
Alto mm (ft)	1.540 (5,1)	1.790 (5,9)	1.900 (6,2)
Anchura de trabajo m (ft)	1,7 (5,5)	1,8 (6,0)	2,1 (6,9)
Volumen balde m ³ (cu.ft)	0,28 (9,9)	0,32 (11,3)	0,38 (13,4)
Capacidad de carga kg (lb)	600 (1.322)	800 (1.763)	1.200 (2.645)
Altura de elevación m (ft)	2,7 (8,9)	2,9 (9,5)	3,2 (10,5)
Potencia requerida cv (hp)	45- 55 (44,4 - 54,2)	60- 75 (59,2 - 73,9)	90- 100 (88,7 - 98,6)

ROTOCULTIVADORES



MODELO	G1GN-125	G1GN-140	G1GN-150	G1GN-160
Anchura de trabajo m (ft)	1,3 (4,1)	1,4 (4,6)	1,5 (4,9)	1,6 (5,2)
Profundidad de trabajo campo seco cm (in)	8,0-14,0 (3,1-5,5)	8,0-14,0 (3,1-5,5)	8,0-14,0 (3,1-5,5)	8,0-14,0 (3,1-5,5)
Profundidad de trabajo arrozal cm (in)	14,0-16,0(5,5-6,3)	14,0-16,0(5,5-6,3)	14,0-16,0(5,5-6,3)	14,0-16,0(5,5-6,3)
Longitud mm (ft)	900 (3,0)	900 (3,0)	900 (3,0)	900 (3,0)
Ancho mm (ft)	1.360 (4,5)	1.690 (5,5)	1.700 (5,6)	1.880 (6,2)
Alto mm (ft)	1.090 (3,6)	1.090 (3,6)	1.090 (3,6)	1.090 (3,6)
Peso operativo kg (lb)	182 (401,2)	214 (471,8)	240 (529,1)	260 (573,2)
Productividad ha/h (ac/h)	0,3-0,5 (0,6-0,9)	0,3-0,5 (0,6-0,9)	0,4-0,6 (0,7-1,1)	0,4-0,6 (0,8-1,2)
Potencia requerida cv (hp)	18-30 (17,7-29,6)	20-30 (19,7-29,6)	25-30 (24,6-29,6)	30-45,5 (29,6-44,9)

ARADOS DE DISCOS



MODELO	G1LY-325	G1LY-425	G1LY-525	G1LY-625	G1LY-530
Anchura de trabajo m (ft)	0,8 (2,5)	1,0 (3,3)	1,3 (4,1)	1,5 (4,9)	1,5 (4,9)
Profundidad de trabajo cm (in)	25 (9,8)	25 (9,8)	25 (9,8)	25 (9,8)	30 (11,8)
Piezas del disco	3	4	5	6	5
Diámetro mm (in)	600 (23,6)	600 (23,6)	600 (23,6)	600 (23,6)	710 (28,0)
Peso operativo kg (lb)	430 (948)	520 (1,146)	600 (1,322)	700 (1,543)	620 (1,366)
Potencia igualada cv (hp)	50-65 (49,3-64,1)	65-85 (64,1-83,8)	80-100 (78,9-98,6)	100-120 (98,6-118,3)	90-120 (88,7-118,3)

ARADOS DE CUCHILLAS



MODELO	25			30G			
Numero de cuchillas	3 cuchillas	4 cuchillas	5 cuchillas	3 cuchillas	4 cuchillas	5 cuchillas	6 cuchillas
Ancho de corte mm (in)	250 (9,8)	250 (9,8)	250 (9,8)	300 (11,8)	300 (11,8)	300 (11,8)	300 (11,8)
Ancho mm (in)	750 (29,5)	1,000 (39,4)	1,250 (49,2)	900 (35,4)	1,200 (47,2)	1,500 (59,1)	1,800 (70,9)
Potencia kw (hp)	40 (53,6)	60 (80,5)	70 (93,9)	55 (73,8)	65 (87,2)	90 (120,7)	110 (147,5)

MODELO	35G			
Numero de cuchillas	3 cuchillas	4 cuchillas	5 cuchillas	6 cuchillas
Ancho de corte mm (in)	350 (13,8)	350 (13,8)	350 (13,8)	350 (13,8)
Ancho mm (in)	1,050 (41,3)	1,400 (55,1)	1,750 (68,9)	2,100 (82,7)
Potencia kw (hp)	65 (87,2)	80 (107,3)	120 (160,9)	120 (160,9)

SEBRADORAS DE TRIGO



MODELO	G2BFX-16	G2BFX-24
Peso operativo kg (lb)	500 (1.102,3)	700 (1.543,2)
Ancho de perforación mm (ft)	2.400 (7,9)	3.600 (11,8)
Filas de perforación	16	24
Profundidad de perforación mm (in)	40-80 (1,6-3,1)	40-80 (1,6-3,1)
Volumen de la caja semilla L (cu.ft)	200 (7,1)	300 (10,6)
Productividad ha/h (ac/h)	1,1-1,6(2,1-3,2)	1,6-2,7(3,2-5,3)
Potencia igualada cv (hp)	50-60 (49,3-59,2)	60-90 (59,2-88,7)

COSECHADORAS DE MAÍZ



MODELO	G4YW-2	G4YW-2
Numero de filas	2	3
Distancia entre filas mm (in)	450-900 (17,7-35,4)	550-850 (21,7-33,5)
Altura mm (ft)	600 (2,0)	600 (2,0)
Ancho mm (ft)	1,400-1,650 (4,6-5,4)	1,650-1,800 (5,4-5,9)
Productividad ha/h (ac/h)	0,3-0,4 (0,5-0,8)	0,3-0,5 (0,5-1,1)
Potencia igualada cv (hp)	50-70 (49,3-69,0)	70-90 (69,3-88,7)
Ratio de corte	Mayor a 90%	Mayor a 90%
Rompimiento de corte	Menor a 2%	Menor a 2%
Tasa de perdida	Menor a 2%	Menor a 2%